

# LED cordless building site spotlight 18.0 V

### CL 2000 18.0



#### Order number 472.921

Technical attributes		
Battery voltage	18 V	
Battery capacity	2,5 / 5,0 Ah	
Luminous flux	1200 / 2000 lm	
Size (W x L x H)	193 x 230 x 190 mm	
Weight without battery	2,4 kg	

#### LED cordless building site spotlight 18.0 V

+ Powerful cordless construction site light with two brightness settings, 1,200 and 2,000 lumen

- + Lamp can be turned through 360°
- + 5/8" connection thread for tripods
- + With optional wall fastening
- + Rugged and long-life for heavy-duty use
- + LED battery capacity display

+ Visual early-warning system: low battery charge is indicated by slightly decreasing level of brightness

+ FLEX battery system: suitable for all FLEX 18,0 V battery packs. Delivery does not include battery and charger

#### Accessories

# Li-Ion rechargeable battery pack 18,0 V

# 18V inna less

#### Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

FLEX

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

# Li-Ion rechargeable battery pack 18,0 V



#### Order number 445.894

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

#### Accessories

# **Rapid charger**

Order number 417.882



Technical attributesQTY/PKG1

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10.8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

#### Power 55 R



Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

#### Order number 491.349

Technical attributes		
QTY/PKG	1	

# FLEX

# Accessories

### Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

# FLEX

#### Order number 491.357

Technical attributes		
QTY/PKG	1	