

## 1010 watt 1-speed mixer with accelerator trigger switch

**MXE 1000 + WR2 120**

**Order number 495.883**



### Technical attributes

No load speed	0-780 rpm
Power input	1010 watt
Power output	550 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	120 mm
Cable length	4,0 m
Size (W x L x H)	405 x 215 x 340 mm
Weight (without mixing paddle)	4,5 kg

### 1010 watt 1-speed mixer with accelerator trigger switch

- + Large, rugged single-speed gear unit with optimum gear ratio for high torque
- + Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- + On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + For mixed applications up to 40 kg
- + Proven standard mixer is ideal for users operating mainly in the low speed range
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...

### Standard equipment

1 WR2 helix paddle 120x600 M14	368.881
1 open-ended wrench SW 19	439.967
1 open-ended wrench SW 22	439.975

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Spiral paddle RR2

Order number 368.903



#### Technical attributes

Paddle in mm	120 Ø
Mix in kg	20-40
QTY/PKG	1

Two negatively arranged spirals force the material down, preventing the liquid material from splashing. Ideal for mixing liquid to tough material: Paint, emulsions, varnishes, glazes, coatings, paste, bitumen.

### Helix paddle WR2

Order number 368.881



#### Technical attributes

Paddle in mm	120 Ø
Mix in kg	15-25
QTY/PKG	1

Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Helix paddle WR3R

Order number 368.911



Technical attributes	
Paddle in mm	120 Ø
Mix in kg	15-25
QTY/PKG	1

Three clockwise helices screw themselves into the material. This provides fast, intensive mixing of even the heaviest and toughest mixtures, with little effort. Also known as a mortar or tough mixture paddle. Ideal for: mortar, concrete, plaster, screed, plasterboard bonding compound, bitumen coating.

### Helix paddle WR3L

Order number 369.055



Technical attributes	
Paddle in mm	120 Ø
Mix in kg	15-25
QTY/PKG	1

Three anticlockwise helices press down the mix in the container. Any deposited pigments, solids or fibres are forced upwards and evenly mixed. The mix does not splash. Ideal for liquid and creamy mix: paints, emulsion paints, gypsum plaster, casting compounds, fibrous materials.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Disc paddle SR2

Order number 368.938



Technical attributes	
Paddle in mm	120 Ø
Mix in kg	15-25
QTY/PKG	1

Two discs with counter-running angled blades create a dynamic flow in the mixing container. The blades on the discs force the material being mixed in opposing directions downwards or upwards. Ideal for mixing liquid to tough material: Paint, emulsion, paste, glue, jointing mortar.

### Beater RB

Order number 369.152



Technical attributes	
Paddle in mm	120 Ø
Mix in kg	10-30
QTY/PKG	1

Round mixing arms prevent air bubbles from being mixed in. Ideal for all materials where air pockets are to be avoided: filler compounds, fillers, adhesives, sealants.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Mixing paddle, M 14

Order number 124.761



For larger quantities. Used with an extension rod.

#### Technical attributes

Dimensions in mm	120 Ø
QTY/PKG	1

### Mixing paddle, M 14

Order number 124.753



For smaller quantities. Used with an extension rod.

#### Technical attributes

Dimensions in mm	70 Ø
QTY/PKG	1