



# SAFETY DATA SHEET

Version #: 1,0

Issue date: 10-November-2022

Revision date: 10-November-2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** Dry Moly Lube

**Registration number** -

**Synonyms** None.

**Product code** UDS000419AE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lubricants

**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

**Company name** CRC Industries Europe bv

**Address** Touwslagerstraat 1  
9240 Zele  
Belgium

**Telephone** +32(0)52/45.60.11

**Fax** +32(0)52/45.00.34

**E-mail** hse@crcind.com

**Website** www.crcind.com

**1.4. Emergency telephone number** Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

**Austria National Poisons Information Centre** +431 406 4343 (Available 24 hours a day.)

**Belgium National Poisons Control Center** 070 245 245 (Available 24 hours a day.)

**Bulgaria National Toxicological Information Centre** +359 2 9154233 (Available 24 hours a day.)

**Czech Republic National Poisons Information Centre** +420 224 919 293, or +420 224 915 402 (Hours of operation not provided.)

**Denmark National Poisons Control Center** +45 82 12 12 12 (Available 24 hours a day.)

**Estonia National Poisons Information Centre** 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays))

**Finland National Poison Information Center** (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day.)

**France National Poisons Control Center** ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day.)

**Hungary National Emergency Phone Number** 36 80 20 11 99 (Available 24 hours a day.)

**Lithuania Neatidėliotina informacija apsinuodijus** +370 5 236 20 52 or +37068753378 (Hours of operation not provided.)

**Malta Accident and Emergency Department** 2545 4030 (Hours of operation not provided.)

<b>Netherlands National Poisons Information Center (NVIC)</b>	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
<b>Norway Norwegian Poison Information Center</b>	22 59 13 00 (Available 24 hours a day.)
<b>Portugal Poison Centre</b>	800 250 250 (Available 24 hours a day.)
<b>Romania Număr de telefon care poate fi apelat în caz de urgență:</b>	021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentafloreasca.ro
<b>Romania</b>	0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro
<b>Slovakia National Toxicological Information Centre</b>	+421 2 5477 4166 (Available 24 hours a day.)
<b>Sweden National Poison Information Center</b>	112 - and ask for Poison Information (Available 24 hours a day.)
<b>Switzerland Tox Info Suisse</b>	145 (Available 24 hours a day.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

<b>Physical hazards</b>			
Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.	
<b>Health hazards</b>			
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.	

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** acetone; propan-2-one; propanone, butanone; ethyl methyl ketone

#### Hazard pictograms



#### Signal word

Danger

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

##### Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P271	Use only outdoors or in a well-ventilated area.

##### Response

Not assigned.

##### Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

## Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information** EUH066 - Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
acetone; propan-2-one; propanone	10 - 30	67-64-1 200-662-2	01-2119471330-49	606-001-00-8	#
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336 <b>Supplemental Hazard Statement(s):</b> EUH066					
butanone; ethyl methyl ketone	1 - 10	78-93-3 201-159-0	01-2119457290-43	606-002-00-3	#
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336 <b>Supplemental Hazard Statement(s):</b> EUH066					
xylene	1 - 10	1330-20-7 215-535-7	-	601-022-00-9	#
<b>Classification:</b> Flam. Liq. 3;H226, Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Acute Tox. 4;H332;(ATE: 11 mg/l), Skin Irrit. 2;H315					

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 4.1. Description of first aid measures

##### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

##### Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

##### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Ingestion

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

#### General fire hazards

Extremely flammable aerosol.

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

##### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

#### Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

#### Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

#### For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
acetone; propan-2-one; propanone (CAS 67-64-1)	MAK	1200 mg/m <sup>3</sup>	
		500 ppm	
	STEL	4800 mg/m <sup>3</sup> 2000 ppm	
bis(sulfanylidene)molybdenum (CAS 1317-33-5)	MAK	5 mg/m <sup>3</sup>	Inhalable fraction.
	STEL	10 mg/m <sup>3</sup>	Inhalable fraction.
butanone; ethyl methyl ketone (CAS 78-93-3)	MAK	295 mg/m <sup>3</sup>	
		100 ppm	
	STEL	590 mg/m <sup>3</sup> 200 ppm	

**Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

Components	Type	Value	Form
xylene (CAS 1330-20-7)	MAK	221 mg/m <sup>3</sup>	
		50 ppm	
	STEL	442 mg/m <sup>3</sup>	
		100 ppm	

**Belgium. Exposure Limit Values**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	1187 mg/m <sup>3</sup>
		492 ppm
	TWA	594 mg/m <sup>3</sup>
		246 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
		300 ppm
	TWA	600 mg/m <sup>3</sup>
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	1400 mg/m <sup>3</sup>
	TWA	600 mg/m <sup>3</sup>
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	885 mg/m <sup>3</sup>
	TWA	590 mg/m <sup>3</sup>
xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	MAC	1210 mg/m <sup>3</sup>
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	MAC	600 mg/m <sup>3</sup>
		200 ppm
	STEL	900 mg/m <sup>3</sup>
		300 ppm
xylene (CAS 1330-20-7)	MAC	221 mg/m <sup>3</sup>
		50 ppm
	STEL	442 mg/m <sup>3</sup>
		100 ppm

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	Ceiling	1500 mg/m <sup>3</sup>

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
	TWA	800 mg/m3
bis(sulfanylidene)molybdenum (CAS 1317-33-5)	Ceiling	25 mg/m3
	TWA	5 mg/m3
butanone; ethyl methyl ketone (CAS 78-93-3)	Ceiling	900 mg/m3
	TWA	600 mg/m3
xylene (CAS 1330-20-7)	Ceiling	400 mg/m3
	TWA	200 mg/m3

**Denmark. Exposure Limit Values**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TLV	600 mg/m3
		250 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	TLV	145 mg/m3
		50 ppm
xylene (CAS 1330-20-7)	TLV	109 mg/m3
		25 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	450 mg/m3
		100 ppm
	TWA	200 mg/m3
		50 ppm

**Finland. Workplace Exposure Limits**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	1500 mg/m3
		630 ppm
	TWA	1200 mg/m3
		500 ppm
bis(sulfanylidene)molybdenum (CAS 1317-33-5)	TWA	0,5 mg/m3
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	300 mg/m3
		100 ppm
	TWA	60 mg/m3
		20 ppm
xylene (CAS 1330-20-7)	STEL	440 mg/m3
		100 ppm
	TWA	220 mg/m3
		50 ppm

**France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	VLE	2420 mg/m3
		1000 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	VME	1210 mg/m3
		500 ppm
	VLE	900 mg/m3
xylene (CAS 1330-20-7)		300 ppm
	VME	600 mg/m3
	VLE	200 ppm
		442 mg/m3
	VLE	100 ppm
	VME	221 mg/m3
		50 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	VLE	2420 mg/m3
	<b>Regulatory status:</b> Regulatory binding (VRC)	
		1000 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	
bis(sulfanylidene)molybden um (CAS 1317-33-5)	VME	1210 mg/m3
	<b>Regulatory status:</b> Regulatory binding (VRC)	
		500 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	
butanone; ethyl methyl ketone (CAS 78-93-3)	VLE	10 mg/m3
	<b>Regulatory status:</b> Indicative limit (VL)	
	VME	5 mg/m3
	<b>Regulatory status:</b> Indicative limit (VL)	
xylene (CAS 1330-20-7)	VLE	900 mg/m3
	<b>Regulatory status:</b> Regulatory binding (VRC)	
		300 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	
	VME	600 mg/m3
	<b>Regulatory status:</b> Regulatory binding (VRC)	
		200 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	
	VLE	442 mg/m3
	<b>Regulatory status:</b> Regulatory binding (VRC)	
		100 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	
	VME	221 mg/m3
	<b>Regulatory status:</b> Regulatory binding (VRC)	
		50 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1200 mg/m3
		500 ppm

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
butanone; ethyl methyl ketone (CAS 78-93-3)	TWA	600 mg/m <sup>3</sup>
		200 ppm
xylene (CAS 1330-20-7)	TWA	220 mg/m <sup>3</sup>
		50 ppm

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

<b>Components</b>	<b>Type</b>	<b>Value</b>
acetone; propan-2-one; propanone (CAS 67-64-1)	AGW	1200 mg/m <sup>3</sup>
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	AGW	600 mg/m <sup>3</sup>
		200 ppm
xylene (CAS 1330-20-7)	AGW	220 mg/m <sup>3</sup>
		50 ppm

**Greece. OELs (Decree No. 90/1999, as amended)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	3560 mg/m <sup>3</sup>
	TWA	1780 mg/m <sup>3</sup>
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
	TWA	300 ppm
xylene (CAS 1330-20-7)	TWA	600 mg/m <sup>3</sup>
	TWA	200 ppm
	STEL	650 mg/m <sup>3</sup>
	STEL	150 ppm
xylene (CAS 1330-20-7)	TWA	435 mg/m <sup>3</sup>
	TWA	100 ppm

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

<b>Components</b>	<b>Type</b>	<b>Value</b>
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
	STEL	900 mg/m <sup>3</sup>
butanone; ethyl methyl ketone (CAS 78-93-3)	TWA	600 mg/m <sup>3</sup>
	STEL	442 mg/m <sup>3</sup>
xylene (CAS 1330-20-7)	TWA	221 mg/m <sup>3</sup>
	TWA	221 mg/m <sup>3</sup>

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	600 mg/m <sup>3</sup>
		250 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
		300 ppm
xylene (CAS 1330-20-7)	TWA	145 mg/m <sup>3</sup>
		50 ppm
	STEL	442 mg/m <sup>3</sup>
		100 ppm
TWA	109 mg/m <sup>3</sup>	

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value
		25 ppm

**Ireland. Occupational Exposure Limits**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Italy. Occupational Exposure Limits**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	200 mg/m3
		67 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	2420 mg/m3
		1000 ppm
	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Netherlands. OELs (binding)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	2420 mg/m3
	TWA	1210 mg/m3
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
	TWA	590 mg/m3
xylene (CAS 1330-20-7)	STEL	442 mg/m3
	TWA	210 mg/m3

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TLV	295 mg/m3
		125 ppm

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
butanone; ethyl methyl ketone (CAS 78-93-3)	TLV	220 mg/m <sup>3</sup>
		75 ppm
xylene (CAS 1330-20-7)	TLV	108 mg/m <sup>3</sup>
		25 ppm

**Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	1800 mg/m <sup>3</sup>
	TWA	600 mg/m <sup>3</sup>
bis(sulfanylidene)molybdenum (CAS 1317-33-5)	STEL	10 mg/m <sup>3</sup>
	TWA	4 mg/m <sup>3</sup>
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
	TWA	450 mg/m <sup>3</sup>
xylene (CAS 1330-20-7)	STEL	200 mg/m <sup>3</sup>
	TWA	100 mg/m <sup>3</sup>

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
	TWA	300 ppm
xylene (CAS 1330-20-7)	TWA	600 mg/m <sup>3</sup>
		200 ppm
	STEL	442 mg/m <sup>3</sup>
	TWA	100 ppm
	221 mg/m <sup>3</sup>	
	50 ppm	

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	300 ppm
	TWA	200 ppm
xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
	TWA	300 ppm
	TWA	600 mg/m <sup>3</sup>
		200 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	TWA	221 mg/m3
		50 ppm

**Spain. Occupational Exposure Limits**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	1200 mg/m3
		500 ppm
	TWA	600 mg/m3
		250 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	Ceiling	900 mg/m3

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value
		300 ppm
	TWA	150 mg/m3
		50 ppm
xylene (CAS 1330-20-7)	Ceiling	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	2400 mg/m3	
		1000 ppm	
	TWA	1200 mg/m3	
		500 ppm	
bis(sulfanylidene)molybden um (CAS 1317-33-5)	TWA	5 mg/m3	Inhalable fraction.
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	590 mg/m3	
		200 ppm	
	TWA	590 mg/m3	
		200 ppm	
xylene (CAS 1330-20-7)	STEL	870 mg/m3	
		200 ppm	
	TWA	435 mg/m3	
		100 ppm	

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	3620 mg/m3
		1500 ppm
	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	899 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm
xylene (CAS 1330-20-7)	STEL	441 mg/m3
		100 ppm
	TWA	220 mg/m3
		50 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
acetone; propan-2-one; propanone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	900 mg/m3
		300 ppm
	TWA	600 mg/m3
		200 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
xylene (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

**Biological limit values**

**Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	20 mg/g	Acetone	Creatinine in urine	*
	20 mg/l	Acetone	Blood	*
	0,34 mmol/l	Acetone	Blood	*
	39 mmol/mol	Acetone	Creatinine in urine	*
butanone; ethyl methyl ketone (CAS 78-93-3)	2,6 mg/g	methyl ethyl ketone	Creatinine in urine	*
	4,08 mmol/mol	methyl ethyl ketone	Creatinine in urine	*
xylene (CAS 1330-20-7)	1,5 g/g	Methylhippuric acids	Creatinine in urine	*
	1,5 mg/l	xylene	Blood	*
	0,88 mol/mol	Methylhippuric acids	Creatinine in urine	*
	14,13 umol/l	xylene	Blood	*

\* - For sampling details, please see the source document.

**Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.**

Components	Value	Determinant	Specimen	Sampling Time
xylene (CAS 1330-20-7)	820 µmol/mmol	Methylhippuric acids	Creatinine in urine	*
	1400 mg/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health**

Components	Value	Determinant	Specimen	Sampling Time
xylene (CAS 1330-20-7)	5 mmol/l	Methylhippuric acids	Urine	*

\* - For sampling details, please see the source document.

**France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	100 mg/l	Acétone	Urine	*
butanone; ethyl methyl ketone (CAS 78-93-3)	2 mg/l	Méthyléthylcétone	Urine	*
xylene (CAS 1330-20-7)	1500 mg/g	Acides méthyhippuriques	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	80 mg/l	ACETON	Urine	*
butanone; ethyl methyl ketone (CAS 78-93-3)	150 mg/l	2-Butanon	Urine	*
xylene (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-) säure (alle Isomere)	Urine	*

\* - For sampling details, please see the source document.

**Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	1380 µmol/l	Acetone	Urine	*
	80 mg/l	Acetone	Urine	*
butanone; ethyl methyl ketone (CAS 78-93-3)	28 µmol/l	MEK	Urine	*
	2 mg/l	MEK	Urine	*
xylene (CAS 1330-20-7)	860 µmol/mmol	methyl hippuric acids	Creatinine in urine	*
	1500 mg/g	methyl hippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	53,36 mg/g	Acetone	Creatinine in urine	*
	80 mg/l	Acetone	Urine	*
xylene (CAS 1330-20-7)	1334 mg/g	Methylhippuric acids	Creatinine in urine	*
	2000 mg/l	Methylhippuric acids	Urine	*
	1,5 mg/l	xylene	Blood	*

\* - For sampling details, please see the source document.

**Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	50 mg/l	Acetona	Urine	*
butanone; ethyl methyl ketone (CAS 78-93-3)	2 mg/l	Metiletilcetona	Urine	*
xylene (CAS 1330-20-7)	1 g/g	Ácidos metilhipúricos	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)**

Components	Value	Determinant	Specimen	Sampling Time
acetone; propan-2-one; propanone (CAS 67-64-1)	80 mg/l	ACETON	Urine	*
butanone; ethyl methyl ketone (CAS 78-93-3)	2 mg/l	2-Butanon (MEK)	Urine	*
xylene (CAS 1330-20-7)	2 g/l	Methyl-Hippurs äure	Urine	*

\* - For sampling details, please see the source document.

**UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling Time
butanone; ethyl methyl ketone (CAS 78-93-3)	70 umol/l	Butan-2-one	Urine	*
xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)**

**General population**

Components	Value	Assessment factor	Notes
acetone; propan-2-one; propanone (CAS 67-64-1)			
Long-term, Systemic, Dermal	62 mg/kg bw/day	20	
Long-term, Systemic, Inhalation	200 mg/m <sup>3</sup>	5	
Long-term, Systemic, Oral	62 mg/kg bw/day	2	

butanone; ethyl methyl ketone (CAS 78-93-3)			
Long-term, Systemic, Dermal	412 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	106 mg/m <sup>3</sup>	2	Repeated dose toxicity

### Workers

Components	Value	Assessment factor	Notes
acetone; propan-2-one; propanone (CAS 67-64-1)			
Long-term, Systemic, Dermal	186 mg/kg bw/day		
Long-term, Systemic, Inhalation	1210 mg/m <sup>3</sup>		
Short-term, Local, Inhalation	2420 mg/m <sup>3</sup>		
butanone; ethyl methyl ketone (CAS 78-93-3)			
Long-term, Systemic, Dermal	1161 mg/kg bw/day	1	Repeated dose toxicity
Long-term, Systemic, Inhalation	600 mg/m <sup>3</sup>	1	Repeated dose toxicity

### Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
acetone; propan-2-one; propanone (CAS 67-64-1)			
Freshwater	10,6 mg/l	50	
Marine water	1,06 mg/l	500	
Sediment (freshwater)	30,4 mg/kg		
Sediment (marine water)	3,04 mg/kg		
Soil	29,5 mg/kg		
STP	100 mg/l	10	
butanone; ethyl methyl ketone (CAS 78-93-3)			
Freshwater	55,8 mg/l	1	
Secondary poisoning	1000 mg/kg	30	Oral
Sediment (freshwater)	284,74 mg/kg		
Soil	22,5 mg/kg	1	

### Exposure guidelines

#### **Austria MAK: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Belgium OELs: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Bulgaria OELs: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Croatia ELVs: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Czech Republic PELs: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Denmark GV: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Estonia OELs: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **EU Exposure Limit Values: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Finland Exposure Limit Values: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **France INRS: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Germany DFG MAK (advisory): Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Germany TRGS 900 Limit Values: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Greece OEL: Skin designation**

xylene (CAS 1330-20-7) Can be absorbed through the skin.

#### **Hungary OELs: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3) Can be absorbed through the skin.  
xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Iceland OELs: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3)  
xylene (CAS 1330-20-7)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Ireland Exposure Limit Values: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3)  
xylene (CAS 1330-20-7)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Italy OELs: Skin designation**

xylene (CAS 1330-20-7)

Danger of cutaneous absorption

**Latvia OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Lithuania OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Luxembourg OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Malta OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Netherlands OELs (binding): Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3)  
xylene (CAS 1330-20-7)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Norway Exposure Limit Values: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Portugal OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Romania OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Slovakia OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

butanone; ethyl methyl ketone (CAS 78-93-3)  
xylene (CAS 1330-20-7)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**Spain OELs: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Sweden Threshold Limit Values: Skin designation**

xylene (CAS 1330-20-7)

Can be absorbed through the skin.

**Switzerland SUVA Limit Values at the Workplace: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3)  
xylene (CAS 1330-20-7)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**UK EH40 WEL: Skin designation**

butanone; ethyl methyl ketone (CAS 78-93-3)  
xylene (CAS 1330-20-7)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**8.2. Exposure controls****Appropriate engineering controls**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment****General information**

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection**

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

**Skin protection****- Hand protection**

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Butyl rubber gloves are recommended. Suitable gloves can be recommended by the glove supplier.

**- Other**

Wear suitable protective clothing.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

<b>Hygiene measures</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
<b>Environmental exposure controls</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Colour</b>	Black.
<b>Odour</b>	Characteristic odor.
<b>Melting point/freezing point</b>	Not available.
<b>Boiling point or initial boiling point and boiling range</b>	56 °C (132,8 °F)
<b>Flammability</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	1,8 %
<b>Explosive limit – upper (%)</b>	13 %
<b>Flash point</b>	-18,0 °C (-0,4 °F)
<b>Auto-ignition temperature</b>	515 °C (959 °F)
<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not applicable.
<b>Kinematic viscosity</b>	Not available.
<b>Solubility</b>	
<b>Solubility (water)</b>	Insoluble in water
<b>Partition coefficient (n-octanol/water) (log value)</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Density and/or relative density</b>	
<b>Relative density</b>	0,84 g/cm <sup>3</sup> 20 °C
<b>Vapour density</b>	Not available.
<b>Particle characteristics</b>	Not available.

### 9.2. Other information

**9.2.1. Information with regard to physical hazard classes** No relevant additional information available.

#### 9.2.2. Other safety characteristics

<b>Evaporation rate</b>	Not available.
<b>VOC</b>	609 g/l

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Acids. Strong oxidising agents. Amines. Ammonia. Caustics. Isocyanates.
<b>10.6. Hazardous decomposition products</b>	Carbon oxides.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
-------------------	---

<b>Skin contact</b>	Based on available data, the classification criteria are not met.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
<b>Symptoms</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### 11.1. Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

Product	Species	Test Results
---------	---------	--------------

Dry Moly Lube

**Acute**

**Dermal**

ATEmix

21996,5 mg/kg bw

Components	Species	Test Results
------------	---------	--------------

acetone; propan-2-one; propanone (CAS 67-64-1)

**Acute**

**Dermal**

LD50

Rat

15800 mg/kg

**Inhalation**

LC50

Rat

50,1 mg/l, 8 Hours

**Oral**

LD50

Rat

5800 mg/kg

butanone; ethyl methyl ketone (CAS 78-93-3)

**Acute**

**Dermal**

LD50

Rabbit

> 8000 mg/kg

**Oral**

LD50

Rat

2300 - 3500 mg/kg

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Causes serious eye irritation.

**Respiratory sensitisation** Based on available data, the classification criteria are not met.

**Skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Risk of cancer cannot be excluded with prolonged exposure.

**Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)**

Not listed.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Mixture versus substance information** Not available.

#### 11.2. Information on other hazards

**Endocrine disrupting properties** The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Other information** Not available.

## SECTION 12: Ecological information

<b>12.1. Toxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>12.2. Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.
<b>12.3. Bioaccumulative potential</b>	
<b>Partition coefficient n-octanol/water (log Kow)</b>	
acetone; propan-2-one; propanone	-0,24
butanone; ethyl methyl ketone	0,29
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
<b>12.6. Endocrine disrupting properties</b>	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
<b>12.7. Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential. GWP: 2
<b>12.8. Additional information</b>	
<b>Estonia Dangerous substances in soil Data</b>	
butanone; ethyl methyl ketone (CAS 78-93-3)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg Chemical pesticides (As the total sum of the active substances) 20 mg/kg Chemical pesticides (As the total sum of the active substances) 5 mg/kg
xylene (CAS 1330-20-7)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg Chemical pesticides (As the total sum of the active substances) 20 mg/kg Chemical pesticides (As the total sum of the active substances) 5 mg/kg

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	Not assigned.
Label(s)	2.1
Hazard No. (ADR)	Not assigned.
Tunnel restriction code	D
ADR/RID - Classification code:	5F
<b>14.4. Packing group</b>	Not assigned.

- 14.5. Environmental hazards** No  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

- 14.1. UN number** UN1950  
**14.2. UN proper shipping name** Aerosols, flammable  
**14.3. Transport hazard class(es)**  
    **Class** 2.1  
    **Subsidiary risk** Not assigned.  
**14.4. Packing group** Not assigned.  
**14.5. Environmental hazards** No  
**ERG Code** 10L  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
    **Passenger and cargo aircraft** Allowed with restrictions.  
    **Cargo aircraft only** Allowed with restrictions.

**IMDG**

- 14.1. UN number** UN1950  
**14.2. UN proper shipping name** Aerosols, flammable  
**14.3. Transport hazard class(es)**  
    **Class** 2.1  
    **Subsidiary risk** Not assigned.  
**14.4. Packing group** Not assigned.  
**14.5. Environmental hazards**  
    **Marine pollutant** No  
**EmS** F-D, S-U  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**14.7. Maritime transport in bulk according to IMO instruments** Not established.

ADR; IATA; IMDG



**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulations**

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**  
Not listed.  
**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**  
Not listed.  
**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**  
Not listed.  
**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**  
Not listed.  
**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**  
Not listed.  
**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**  
Not listed.  
**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**  
acetone; propan-2-one; propanone (CAS 67-64-1)

xylene (CAS 1330-20-7)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

#### Restrictions on use

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see [https://ec.europa.eu/home-affairs/system/files/2021-11/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf).

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

acetone; propan-2-one; propanone (CAS 67-64-1)

butanone; ethyl methyl ketone (CAS 78-93-3)

xylene (CAS 1330-20-7)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

#### Other EU regulations

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

acetone; propan-2-one; propanone (CAS 67-64-1)

butanone; ethyl methyl ketone (CAS 78-93-3)

xylene (CAS 1330-20-7)

#### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

#### National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

#### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

#### References

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any statements, which are not written out in full under sections 2 to 15**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

**Revision information**

None.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.