

211 - FINISHING OIL

FINISHING OIL is a biological oil for treatment and maintenance of wood surfaces like beach, cherry and alder. The oil will underline the natural structure of the wood and provide a beautiful, lasting and resistant surface, protecting against dirt, moisture and drying out. Lighter woods will attain a light yellow color.

Instructions

Apply with a cloth or brush and wipe off excess oil after 1 hour. New or dried-out wood requires repeated treatments, however, the oil must harden (9-12 hours) between each application.

Oil Sanding: A professional finish can be obtained if the surface is sanded in yet a layer of wet oil. Sand in the grain direction and wipe off excess oil after 15 min.

Declaration

Contains: Refined linseed oil, aliphatic hydrocarbons, leadfree siccative and antioxidants.

DANGER: Contains: Aliphatic hydrocarbons: may be fatal if swallowed and enters airways. Flammable liquid and vapor. Contains 2-butanone oxime and fatty acids, branched (C6-C19), cobalt (2+) salts: may produce an allergic reaction.

WARNING: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep cool. Used rags may self-ignite and should therefore be soaked in water and packed air-tight in aluminium foil or in a plastic bag before discarding. Keep out of reach of children.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If medical advice is needed, have product container or label at hand.



Conditioning

250ml (12 units/box) / 500ml (12 units/box)



If you have any questions, please contact our Technical Department on: +45 4817 6970