

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Polisher for small areas

**PE 8-4 80**

Order number 405.817



### Technical attributes

Max. polishing pad diameter	80 mm
Max. back-up pad diameter	75 mm
No load speed	1300-3900 rpm
Power input	800 watt
Power output	425 watt
Tool fixture	M 14
Cable length	4,0 m
Size (W x L x H)	305 x 83 x 105 mm
Weight	1,8 kg

### Polisher for small areas

- + VR electronic control: with tachogenerator constant speed control, soft start, overload protection and speed selection
- + Lightweight and easy-to-use on small surfaces, tight spaces
- + Spindle lock

### Standard equipment

1 side handle	194.034
---------------	---------

## Accessories

### Polish

Order number 443.271



Technical attributes	
Contents	250 ml
QTY/PKG	1

Universal high-performance abrasive paste with maximum removal rate for maximum gloss. Sanding grooves of grain size P 1500 can be removed in seconds. Ideally suited for all paint types, including scratch-resistant paints, UV paints and for treating gliders and motorized aircraft, boat hulls, polycarbonate and wood finishing work. The polish is free of wax, silicone and odorant solvents. Minor holograms might be caused by rotary working on dark paints. These can be polished out with the polish P 03/06-LDX in conjunction with the orange polishing sponge PS-0. Abrasiveness 5 / gloss 5.

### Polish

Order number 443.298



Technical attributes	
Contents	250 ml
QTY/PKG	1

Special polish for removing scratches with a very deep sheen. Sanding grooves of grain size P 2000 can be removed in seconds. Ideal for all paint types, including scratch-resistant paints, UV paints and for freshening up colours in the case of old paints. Optimum results are achieved with eccentric 1-step working, and rotary working is of course also possible. The polish is silicone-free, produces little dust and can be easily rubbed in and wiped off. Abrasiveness 3 / gloss 6.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Sealing

Order number 443.301



#### Technical attributes

Contents	250 ml
QTY/PKG	1

Paintwork-compatible sealant for new and previously polished paints. It's Carnuba wax protects paint against environmental influences, provides care and protects the high sheen. The sealant can be applied both with a machine (rotary/eccentric) using the red polishing sponge PS-R and manually with the red application sponge PUK-R. It contains no abrasive particles and can be painted over. Protective effect 2 / smoothness 4.

### Microfibre polishing cloth, classic

Order number 317.098



#### Technical attributes

Dimensions in mm	400 x 400
QTY/PKG	1

Seamless, washable. For gentle removal of polishing and sealing residues. For a perfect surface finish and brilliant deep gloss.

## Accessories

### Microfibre polishing cloth, premium

Order number 376.531



#### Technical attributes

Dimensions in mm	400 x 400
QTY/PKG	1

Thanks to the very high soft pile, residues can be picked up reliably and gently. This is what makes the microfibre cloth ideal for an optimum paint finish. It can also be used for car wash purposes. Long service life, washing machine safe (without softener).

### Polishing sponge

Order number 442.682



#### Technical attributes


Dimensions in mm	130 Ø
QTY/PKG	1

The red sponge for hand application is ergonomically shaped and has a very soft foam with a fine texture. It is ideally suited to working with sealants and care agents on painted and plastic surfaces, for hard-to-reach places or sensitive surfaces that are difficult to deal with by using a machine.

## Accessories

### Velcro pad, cushioned M 14

Order number 446.254



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

#### Technical attributes

Dimensions in mm	35 Ø
QTY/PKG	1

### Velcro pad, cushioned M 14

Order number 420.492



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

#### Technical attributes

Dimensions in mm	75 Ø
QTY/PKG	1

### Polishing sponge

Order number 442.631



The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut

#### Technical attributes

Dimensions in mm	40 Ø x 25
QTY/PKG	2

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

## Polishing sponge

Order number 434.264



Technical attributes	
Dimensions in mm	80 Ø x 25
QTY/PKG	2

The green sponge has a very hard foam with an innovative X-Cut surface that guarantees a constant and evenly high removal rate. The X-Cut texture reduces the building-up of heat. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

## Polishing sponge

Order number 442.658



Technical attributes	
Dimensions in mm	40 Ø x 25
QTY/PKG	2

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

## Accessories

### Polishing sponge

Order number 434.442



#### Technical attributes

Dimensions in mm	80 Ø x 25
QTY/PKG	2

The violet sponge has a hard foam for optimum cooling and guarantees a constant and evenly high removal rate. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with water droplets, orange peel, trapped dust, tar specks, scratches and bird droppings in conjunction with the P05/05-LDX.

### Polishing sponge

Order number 442.666



#### Technical attributes

Dimensions in mm	40 Ø x 25
QTY/PKG	2

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

## Accessories

### Polishing sponge

Order number 434.302



#### Technical attributes

Dimensions in mm	80 Ø x 25
QTY/PKG	2

The orange sponge has a medium-hardness foam with a fine foam texture. The foam is heat-resistant, tear-resistant and has very good endurance. Ideal for dealing with holograms, matting, scratches and car wash traces in conjunction with the P 03/06-LDX.

### Polishing sponge

Order number 442.674



#### Technical attributes

Dimensions in mm	40 Ø x 25
QTY/PKG	2

The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.

## Accessories

### Polishing sponge

Order number 434.345



#### Technical attributes

Dimensions in mm	80 Ø x 25
QTY/PKG	2

The red sponge has a very soft foam with a fine foam texture. The special PerfectTouch sandwich structure with an additional stronger white foam layer gives the sponge greater rigidity. This configuration increases the service life of the polishing disk. Ideal for dealing with holograms and slight matting in conjunction with the P 03/06-LDX, for paintwork care and sealing in conjunction with the W 02/04.

### Polishing lambswool, premium

Order number 420.484



#### Technical attributes

Dimensions in mm	80 Ø
QTY/PKG	1

Polishing lambswool consisting of 90% natural wool and 10% polyester. This combination provides for longer service life and greater volume. And it can remove sanding scratches, for example, 30% faster than with using a sponge. Ideal for UV paints and the latest generation of scratch-resistant paints. For a great polishing effect in combination with the fine polishing compound. The special PerfectTouch sandwich design and extra orange foam layer gives the pad that slight degree of cushioning and much greater stiffness. This allows for a perfect surface contact even in problem areas and an optimal and exact guiding.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Carrying bag for polisher

Order number 333.573



#### Technical attributes

QTY/PKG	1
---------	---

Practical mobile carry bag offer lots of room for machine and accessories, with variable pockets.

### Extension set for rotary polisher

Order number 458.813



#### Technical attributes

QTY/PKG	1 set
---------	-------

Rotary polisher extensions to facilitate work in narrow and difficult to reach areas such as exterior mirrors, spoilers, bumpers, etc. Comprises three M14 anodized aluminium extensions in 50 mm, 80 mm, 120 mm and one M14 adapter for cordless screwdrivers. Shaft  $\varnothing$  19 mm, width across flat SW 17, max. backing pad  $\varnothing$  75 mm, max. polishing disc  $\varnothing$  80 mm. Packaged in the practical Mini L-BOXX® with insert and separate compartment for the Swirl Finder SF 150-P LED light (not included).

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Swirl Finder Pocket Light

Order number 463.302



#### Technical attributes

QTY/PKG	1
Size (W x L x H)	190 x 58 x 43 mm
Weight	0,056 kg

LED light for easy control of surface conditions. Due to the colour temperature and reproduction, surface damage such as holograms, scratches etc. become better visible. Light intensity 140 lumens and adjustable focus with a beam angle of 10° -70°, lighting time approx. 2 hours incl. batteries.