

FLEX-Elektrowerkzeuge GmbH  
 Bahnhofstraße 15  
 71711 Steinheim  
 Phone +49 7144 828-0  
 Fax +49 7144 25899  
 info@flex-tools.com  
 www.flex-tools.com

# FLEX

## Pipe belt sander TRINOXFLEX Set

**BRE 14-3 125 Set**

**Order number 433.446**



Technical attributes	
Power input	1400 watt
Power output	880 watt
Belt speed	3,5-10 m/sec
Belt dimensions	760 x 40 mm
Pipe Ø max.	125 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Size (W x L x H)	520 x 160 x 220 mm
Weight	3,6 kg

### Pipe belt sander TRINOXFLEX Set

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Sanding belt replacement: quick and tool-free
- + Sanding belt dimension: 760 x 40 mm
- + High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- + Spindle lock

Standard equipment	
1 sanding attachment, pipe belt BR 125	433.470
1 sanding-polishing belt S 600	326.917
1 superfinishing band S 1500	326.933
1 sanding belt MESHFLEX A 240	1 piece of 326.879
1 sanding belt MESHFLEX A 400	1 piece of 326.852
5 sanding belts CORUFLEX P 80	5 pieces of 326.739
5 sanding belts CORUFLEX P 120	5 pieces of 326.755
5 sanding belts CORUFLEX P 240	5 pieces of 434.914
1 carrying case L-BOXX® 238	414.093
1 case insert	433.918

## Accessories

### Sanding attachment, burnishing

Order number 433.462




Sanding attachment with integrated handle for burnishing. For the TRINOXFLEX. Tool-free fitting via the quick-change system.

#### Technical attributes

QTY/PKG	1
---------	---

### Sanding attachment, pipe belt

Order number 433.470



Sanding attachment for pipe belt sanding. For the TRINOXFLEX. Tool-free fitting via the quick-change system. Variably adjustable attachment.

#### Technical attributes

QTY/PKG	1
---------	---

### Sanding attachment, brushing

Order number 461.555



Grinding & brushing attachment for the TRINOXFLEX. With removable protective hood and suction connection Ø 32 mm for low-dust work.

#### Technical attributes

QTY/PKG	1
---------	---

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

Including guide stop and vibration-damped ergonomic handle. Tool-free change of grinding tool via a patented quick-change system

## Extraction hood

Order number 461.547



Extraction hood for the BSE 14-3 100 with extraction connection (D32 clip) for rollers and brushes with max. Ø 110 mm.

### Technical attributes

QTY/PKG	1
---------	---

## Sanding belt ZIRCOFLEX



Sanding belt with high-quality, self-sharpening zirconium corundum for a longer service life. High abrasion performance in coarse and intermediate sanding on steel and stainless steel surfaces.

### Technical attributes

Dimensions in mm	Grit	QTY/PKG	Order number
760 x 40	P 36	10	438.464
760 x 40	P 40	10	438.472
760 x 40	P 60	10	438.480
760 x 40	P 80	10	438.499
760 x 40	P 120	10	438.502

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Sanding belt CERAFLEX




#### Technical attributes

Dimensions in mm	Grit	QTY/PKG	Order number
760 x 40	60	10	438.510
760 x 40	80	10	438.529
760 x 40	120	10	438.537

Flexible high-performance sanding belt for optimum sanding performance, with high abrasion performance and an extremely long service life thanks to self-sharpening, micro-crystalline ceramic grit for preliminary and intermediate sanding on stainless steel surfaces. Cool sanding thanks to additional multi-bonding.

### Sanding belt CORUFLEX



#### Technical attributes

Dimensions in mm	Grit	QTY/PKG	Order number
760 x 40	P 80	10	326.739
760 x 40	P 120	10	326.755
760 x 40	P 180	10	434.906
760 x 40	P 240	10	434.914

Highly flexible sanding belt with annealed corundum grit and active-sanding agents for finishing stainless steel. Particularly suitable for finish sanding.

### Sanding belt MESHFLEX



#### Technical attributes

Dimensions in mm	Grit	QTY/PKG	Order number
760 x 40	A 100	3	326.895
760 x 40	A 240	3	326.879
760 x 40	A 400	3	326.852

For removing minor damage, scratches, tarnish, flash rust, scale and dirt. Removing tarnish at welds without heat distortion at thin plates. For grinding, cleaning and finishing stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics.

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Accessories

### Superfinishing band




For high-gloss polishing without polishing agents in two steps.

#### Technical attributes

Dimensions in mm	Grit	QTY/PKG	Order number
760 x 40	S 600	1	326.917
760 x 40	S 1500	1	326.933

### Case insert



Matching insert for BSE/BRE/BSE INOX 14-3 for carry case L-BOXX® 238.

**Order number 433.918**

#### Technical attributes

QTY/PKG	1
---------	---

### Carrying case L-BOXX®



**Order number 414.093**

#### Technical attributes

External dimensions L x W x H	442 x 357 x 253 mm
Internal dimensions L x W x H	378 x 306 x 209 mm
Weight	2,8 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
[info@flex-tools.com](mailto:info@flex-tools.com)  
[www.flex-tools.com](http://www.flex-tools.com)

# FLEX

comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.