

## POLISHFLEX, variable-speed polisher with a high torque

**PE 14-2 150 P-Set**

**Order number 376.175**



### Technical attributes

Max. polishing pad diameter	200 mm
Max. back-up pad diameter	150 mm
No load speed	380-2100 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Cable length	4,0 m
Size (W x L x H)	405 x 84 x 117 mm
Weight	2,3 kg

### POLISHFLEX, variable-speed polisher with a high torque

- + Microprocessor electronics: stepless speed selection, tachogenerator-controlled constant speed, overload protection, re-start protection and temperature monitoring
- + Powerful 1400 watt motor with highly-efficient ventilator for optimum cooling
- + Continuous speed control trigger: for a gentle start (starting speed at setting 1 (380 rpm)) and a lock-on for continuous operation
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Innovative combination of planetary and angular gears reduces noise to an absolute minimum
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + Spindle lock: It is ideally positioned to prevent operating error and does not interfere with the grip area.
- + With rubberised resting bar for safe setting down
- + 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions

### Standard equipment

1 handle	252.721
1 velcro backing pad, cushioned, Ø 150 mm	350.745
1 polishing sponge PS-0 160	434.329
1 polishing sponge PS-V 160	434.469
1 lambswool TW-PT 160	376.523
1 polish P03/06-LDX 250 ml	443.298
1 polish P05/05-LDX 250 ml	443.271
1 microfibre cloth MW-P	376.531
1 carrying case L-BOXX® 238	414.093
1 case insert	444.375