SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation **EASY WELD**

of the mixture

Registration number

Synonyms None

BDS000995AF **Product code** 09-December-2022 Issue date

1 0 Version number

09-December-2022 **Revision date**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Welding Products Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe by Company name

Address Touwslagerstraat 1

> 9240 Zele Belgium

Telephone +32(0)52/45.60.11 +32(0)52/45.00.34 Fax E-mail hse@crcind.com www.crcind.com Website

1.4. Emergency telephone Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure

dizziness.

Environmental hazards

Hazardous to the aquatic environment, H411 - Toxic to aquatic life with Category 2

long-term aquatic hazard long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

hydrocarbons, C6, isoalkanes, < 5% n-hexane, pentane Contains:

Hazard pictograms



Signal word Danger

Material name: EASY WELD - Manufacturers

Hazard statements

Extremely flammable aerosol. H222

Pressurized container: May burst if heated. H229

SDS GREAT BRITAIN

Causes skin irritation. H315

May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

Do not pierce or burn, even after use. P251

Avoid breathing mist/vapours. P261

Use only outdoors or in a well-ventilated area. P271

Response Not assigned.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P410 + P412

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

None.

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation 2.3. Other hazards

(EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
hydrocarbons,C6,isoalkanes,< 5% n-hexane	<50	- 931-254-9	01-2119484651-34	649-328-00-1	
Classification:		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	H315, STOT SE 3;H336, As _l 1	p. Tox.	
pentane	<50	109-66-0 203-692-4	01-2119459286-30	601-006-00-1	#
Classification:	Flam. Liq. Chronic 2		H336, Asp. Tox. 1;H304, Ac	quatic	

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Ingestion May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

4.2. Most important symptoms and effects, both acute and delayed

redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

Material name: EASY WELD - Manufacturers SDS GREAT BRITAIN 5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	
pentane (CAS 109-66-0)	TWA	1800 mg/m3	
		600 ppm	
Biological limit values	No biological exposure limits noted	for the ingredient(s).	

Recommended monitoring procedures

No biological exposure limits noted for the ingredient(s).

Follow standard monitoring procedures.

Material name: EASY WELD - Manufacturers SDS GREAT BRITAIN BDS000995AE Version #: 1.0 Revision date: 09-December-2022 Issue date: 09-December-2022

Derived no effect levels (DNELs)

General population

General population				
Components		Value	Assessment factor	Notes
hydrocarbons,C6,isoalkanes,<	< 5% n-hexane ((CAS -)		
Long-term, Systemic, Der Long-term, Systemic, Inha Long-term, Systemic, Ora	alation	1377 mg/kg bw/day 1131 mg/kg bw/day 1301 mg/kg bw/day		
pentane (CAS 109-66-0)				
Long-term, Systemic, Der Long-term, Systemic, Inha		214 mg/kg bw/day 643 mg/m3	5 5	Repeated dose toxicity Repeated dose toxicity
<u>Workers</u>				
Components		Value	Assessment factor	Notes
hydrocarbons,C6,isoalkanes,<	< 5% n-hexane ((CAS -)		
Long-term, Systemic, Der Long-term, Systemic, Inha		13964 mg/kg bw/day 5306 mg/m3		
pentane (CAS 109-66-0)				
Long-term, Systemic, Der Long-term, Systemic, Inha		432 mg/kg bw/day 3000 mg/m3	3 3	Repeated dose toxicity Repeated dose toxicity
Predicted no effect concentratio	ns (PNECs)			
Components		Value	Assessment factor	Notes
pentane (CAS 109-66-0)				
Freshwater Sediment (freshwater) Soil		230 μg/l 1.2 mg/kg 0.55 mg/kg	1 1 1	
8.2. Exposure controls				
Appropriate engineering controls	applicable, us maintain airbo	e process enclosures, loca orne levels below recomme	al exhaust ventilation, or ot ended exposure limits. If ex	be matched to conditions. If ther engineering controls to kposure limits have not been de eyewash station and safety
Individual protection measures,	such as perso	nal protective equipment	t ·	
General information				on equipment should be chosen or of the personal protective
Eye/face protection	Wear safety g	lasses with side shields (or	r goggles). Use eye proted	ction conforming to EN 166.
Skin protection				
- Hand protection	time of the glo	ove should be longer than t ugh time, gloves should be	he total duration of produc	ard EN 374). The breakthrough ct use. If work lasts longer than h. Nitrile gloves are
- Other	Wear appropr	iate chemical resistant clot	hing.	
Respiratory protection		ufficient ventilation, wear รเ ır cartridge and full facepie		ent. Chemical respirator with
Thermal hazards	Wear appropr	iate thermal protective clot	hing, when necessary.	
Hygiene measures	When using d	o not smoke. Always obset the material and before ea	rve good personal hygiene ating, drinking, and/or smo	e measures, such as washing king. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid. Aerosol. **Form** Colourless. Colour

Characteristic odor. Odour

Odour threshold Not available.

BDS000995AE Version #: 1.0 Revision date: 09-December-2022 Issue date: 09-December-2022

pH Not applicable.Melting point/freezing point Not available.

Initial boiling point and boiling 35 - 65 °C (95 - 149 °F)

range

Flash point -45.0 °C (-49.0 °F) Closed cup

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Explosive limit - upper

7.8 % estimated

Explosive limit – upper (%)

Vapour pressure Not available.

Vapour density > 1 at 15°C

Relative density 0.73 g/cm3 at 20°C

Solubility(ies)

Solubility (water) Insoluble in water

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature> 200 °C (> 392 °F)Decomposition temperatureNot available.Viscosity< 7 mPa·s at 40°C</th>Explosive propertiesNot explosive.

Oxidising properties
9.2. Other information

Kinematic viscosityNot available **VOC**510 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

Not oxidising.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

hydrocarbons, C6, isoalkanes, < 5% n-hexane

<u>Acute</u> Dermal

LD50 Rabbit 3350 mg/kg, 4 h

Material name: EASY WELD - Manufacturers SDS GREAT BRITAIN

Components	Species	Test Results
Inhalation		
LD50	Rat	259354 mg/m3
Oral		
LD50	Rat	16750 mg/kg
pentane (CAS 109-66-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Inhalation		
LC50	Rat	364 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritati	on.
Respiratory sensitisation	Based on available data, the classification criteria are	e not met.
Skin sensitisation	Based on available data, the classification criteria are	e not met.
Germ cell mutagenicity	Based on available data, the classification criteria are	e not met.
Carcinogenicity	Based on available data, the classification criteria are	e not met.
Reproductive toxicity	Based on available data, the classification criteria are	e not met.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are	e not met.
Aspiration hazard	Not likely, due to the form of the product.	
Mixture versus substance information	Not available.	

SECTION 12: Ecological information

12.1. Toxicity	Toxic to a	Toxic to aquatic life with long lasting effects.			
Components		Species	Test Results		
hydrocarbons,C6,isoalkanes,	< 5% n-hexane				
Acute					
Other	EC50	Pseudokirchnerella subcapitata	13.6 mg/l, 72 hours		
	NOEC	Pseudokirchnerella subcapitata	3 mg/l, 72 hours		
Aquatic					
Acute					
Crustacea	EC50	Daphnia magna	31.9 mg/l, 48 hours		
	NOEC	Daphnia magna	7.14 mg/l, 21 days		
Fish	EC50	Rainbow trout	18.3 mg/l, 96 hours		
	NOEC	Rainbow trout	4.09 mg/l, 28 days		
12.2. Persistence and degradability	No data is	s available on the degradability of any ingr	redients in the mixture.		
12.3. Bioaccumulative poter	ntial				
Partition coefficient n-octanol/water (log Kow)					
nentane		3 30			

pentane 3.39

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

(LO) NO 1907/2000, AIRICX XIII.

12.6. Other adverse effectsThe product contains volatile organic compounds which have a photochemical ozone creation

potential. GWP: 3

5

pentane (CAS 109-66-0)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not assigned.

Tunnel restriction code D **ADR/RID - Classification** 5F

code:

14.4. Packing group Not assigned.

14.5. Environmental hazards yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not assigned.

14.5. Environmental hazards yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not assigned.

14.5. Environmental hazards yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable

name

Material name: EASY WELD - Manufacturers

SDS GREAT BRITAIN

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards yes **ERG Code** 10L

14.6. Special precautions Read s

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable, MARINE POLLUTANT

name

for user

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards

Marine pollutant yes EmS F-D, S-U

14.6. Special precautions

5,00

Not established.

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

 Not listed
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended pentane (CAS 109-66-0)

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value. TWA: Time Weighted Average.

VLE: Exposure Limit Value.
VME: Exposure Average Value.
VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References Not available.

Material name: EASY WELD - Manufacturers SDS GREAT BRITAIN

Information on evaluation method leading to the classification of mixture

Full text of any statements, which are not written out in full under sections 2 to 15 The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision information None.

Training information

Disclaimer

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

·

Material name: EASY WELD - Manufacturers SDS GREAT BRITAIN