

# Cordless drywall screwdriver 18,0 V with screw magazine attachment

# DW 45 18.0-EC M/2.5 Set





#### Cordless drywall screwdriver 18,0 V with screw magazine attachment

- + Brushless motor with greater efficiency and a longer service life
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Right/left rotation with safety catch
- + Electronic quick-acting brake
- + Accelerator trigger with lock-off switch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + Ergonomically shaped soft handle with on/off switch and lock for continuous operation
- + LED battery capacity display
- + Tool-free detachable depth stop
- + Screw magazine attachment can be removed without any tools
- + Ergonomic two-handed operation of magazine and drywall screwdriver for reliable and accurate screw joints
- + Including belt clip and bit storage
- + FLEX battery system: suitable for all FLEX 18,0 V battery packs

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. torque	28 Nm
No load speed	0-4500 rpm
Tool fixture	1/4" hexagon socket
Max. screw diameter	4,2 mm
Size (W x L x H)	337 x 75 x 203 mm
Weight without battery	0,975 kg
Weight with battery 2,5 Ah / M-DW 55	1,89 kg

Standard equipment	
1 screw magazine attachment M-DW 55	463.698
1 bit holder UH-M 50 E6,3-C6,3	395.919
1 bit DB PH2 150 E6,3	1 piece of 466.859
1 depth stop	1 piece
1 bit storage	430.862
1 belt clip	467.154
2 batteries 2.5 Ah AP 18.0/2.5	445.886
1 charger CA 10.8/18.0	417.882
1 carrying case L-BOXX <sup>®</sup> 136	414.085
1 case insert	466.840



### **Accessories**

# Screw magazine attachment



#### **Order number 463.698**

Technical attributes	
Weight	0,5 kg
QTY/PKG	1

For standard, belted screws. Screw magazine attachment rotates 360°, making it easy to reach into corners, tool-free screwing depth setting via wheel, tool-free adjustable depth stop to adapt to different screw lengths from 25-55 mm, max. shank diameter 4.2 mm. Ergonomic SoftGrip handles. Fits drywall screwdriver DW 45 18.0-EC.

# Li-Ion rechargeable battery pack 18,0 V



#### Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.



### **Accessories**

# Li-Ion rechargeable battery pack 18,0 V



#### **Order number 445.894**

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

# **Rapid charger**



#### **Order number 417.882**

Technical attributes		
QTY/PKG	1	

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10,8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.



### **Accessories**

## Bit Order number 466.859



Technical attributes	
Dimensions in mm	150
QTY/PKG	3

Design PH size 2, E 6,3. Can be used with screw magazine attachment M-DW 55 (463.698).

### Bit holder




Magnetic, design PH size 2, E 6,3. Can be used with DW 45 18.0-EC.

#### **Order number 395.919**

Technical attributes	
Dimensions in mm	50
QTY/PKG	1

## **Case insert**



Matching insert for DW 45 18.0-EC for carry case L-BOXX® 136.

### **Order number 466.840**

Technical attributes		
QTY/PKG	1	



### **Accessories**

# Carrying case L-BOXX®



#### **Order number 414.085**

Technical attributes	
External dimensions L x W x H	442 x 357 x 151 mm
Internal dimensions L x W x H	378 x 311 x 107 mm
Weight	2,2 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.

## Power 55 R Order number 491.349



Technical attributes		
QTY/PKG	1	

Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.



## **Accessories**

## Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

#### **Order number 491.357**

Technical attributes	
QTY/PKG	1

## **Bit**



Design PH size 2, C 6,3.

#### Order number 395.927

Technical attributes	
Dimensions in mm	25
QTY/PKG	5