

1200 watt 2-speed mixer with 3-level speed switch

MXE 1202 + WR2 140

Order number 495.921



1200 watt 2-speed mixer with 3-level speed switch

- + Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials
- + Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- + Comfortable 3-level switch can be reached from the grip position without interrupting work, protected by a rubber sleeve. Level 1: cleaning, level 2: stirring up, level 3: mixing
- + On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + Spindle lock with start-up protection. Simplifies exchange of the mixing paddle
- + For mixed applications up to 60 kg
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...

Technical attributes

No load speed 1st gear	0-210/325/530 rpm
No load speed 2nd gear	0-320/490/780 rpm
Power input	1200 watt
Power output	710 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	140 mm
Cable length	4,0 m
Size (W x L x H)	405 x 215 x 340 mm
Weight (without mixing paddle)	4,8 kg

Standard equipment

1 helix paddle WR2 140x600 M14	368.997
1 open-ended wrench SW 22	439.975