

307 - STONE OIL

STONE OIL, for the treatment of slate and other porous stone or porous ceramic tiles. The oil impregnates the surface and gives a mat gloss, underlining the natural structure and color. Protects against drying out and prevents smudging, which will make daily cleaning easier.

Instructions

Apply the oil to a clean and dry surface in a uniform layer with a cloth or brush. Wipe excess oil off after 2 hours. Repeat the treatment every day until the surface no longer absorbs oil. The best result is obtained, if the surface - once saturated - is allowed to harden for 24 hours before use.

Declaration

Contains: Pure linseed oil, iso-paraffinic hydrocarbons and antioxidants.

DANGER: Contain: iso-paraffinic hydrocarbons: may be fatal if swallowed and enters airways. Flammable liquid and vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep cool. Used rags may self-ignite and should therefore be soaked in water and packed air-tight in aluminium foil or in a plastic bag before discarding. Keep out of reach of children.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If medical advice is needed, have product container or label at hand.



Conditioning

250ml (12 units/box) / 500ml (12 units/box)

If you have any questions, please contact our Technical Department on: +45 4817 6970