

FLEX-Elektrowerkzeuge GmbH  
 Bahnhofstraße 15  
 71711 Steinheim  
 Phone +49 7144 828-0  
 Fax +49 7144 25899  
 info@flex-tools.com  
 www.flex-tools.com

# FLEX

## Pipe belt sander TRINOXFLEX Set

**BRE 14-3 125 Set**

**Order number 433.446**



### Technical attributes

Power input	1400 watt
Power output	880 watt
Belt speed	3,5-10 m/sec
Belt dimensions	760 x 40 mm
Pipe Ø max.	125 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Size (W x L x H)	520 x 160 x 220 mm
Weight	3,6 kg

### Pipe belt sander TRINOXFLEX Set

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Sanding belt replacement: quick and tool-free
- + Sanding belt dimension: 760 x 40 mm
- + High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- + Spindle lock

### Standard equipment

1 sanding attachment, pipe belt BR 125	433.470
1 sanding-polishing belt S 600	326.917
1 superfinishing band S 1500	326.933
1 sanding belt MESHFLEX A 240	1 piece of 326.879
1 sanding belt MESHFLEX A 400	1 piece of 326.852
5 sanding belts CORUFLEX P 80	5 pieces of 326.739
5 sanding belts CORUFLEX P 120	5 pieces of 326.755
5 sanding belts CORUFLEX P 240	5 pieces of 434.914
1 carrying case L-BOXX® 238	414.093
1 case insert	433.918